

iSAFT Mains Isolation & Transformer Unit (MITU) - Rack Mountable



The iSAFT-MITU is a Power Distribution Unit (PDU), which provides full isolation between the input power source and the output. This unit has been designed to be used as a high protection and filtered element in electrical supply for electronics systems that are part of EGSE / SCOE / ATE etc.

It consists of the Mains Isolation Transformer and Distribution unit, the optional internal rack-mountable remote on/off & EPO panel and the optional external remote on/off & EPO box with the Low Voltage Indicator. Measurements for input and output power are provided on digital displays on the unit's front panel.

The iSAFT-MITU transformer is designed to be powered on with low inrush current without the use of a current limiter, preventing Start-Up Issues without the possibility of power cut off from an input fuse or hardware failure on a current limiter device.

The iSAFT-MITU integrates an Insulation Monitoring Device, which is activated in case of a single failure. Specifically, if any of the power lines gets in contact with the chassis of the equipment, the differential protection of the unit will cut-off the power supply for safety purposes.

Main Features

- Class II Isolation Transformer.
- Input & output measure of voltage & current.
- Low voltage control circuit.
- Power supply cable (10m) with CEE input plug connector.
- 19" Rack mountable.
- Optional rack mountable EPO with remote on/off and/or external EPO with Low Voltage Indicator.
- Optional custom input plug connector and custom power supply cable length.

Competitive advantages

- Start-Up low inrush current.
- Continuous insulation monitoring on the output.
- Separate ground points for input and output.
- Selectable ground schema.
- Double insulation chassis.

Key Benefits

- Proven industrial solution in various EU customers.
- Product series from 1 to 5 KVA Output Power, 1 phase / 3 phase, according to power requirements.
- The iSAFT-MITU has been integrated in various rack based test benches, automated test equipment and EGSEs for the aerospace sector.

Standards

- EN 61558-1:2005/A1:2009
- EN 61558-2-4:2009
- EN 61011-1:2010

Insulation Monitoring

The iSAFT-MITU isolation PDU device is equipped with an Isolation Monitoring Device (IMD). In case of an insulation fault, the IMD switches off completely the isolation PDU after 7 secs through the auxiliary contact, and at the same time the red LED indicating "insulation fault" lights on. The operation of the isolation PDU will be restored only when the insulation is repaired.

Technical Data

iSAFT-MITU-	411 / 413 / 415	435
INPUT		
Phase	Single	Three
Voltage	230VAC	400VAC
Frequency	50-60 Hz	50-60 Hz
Current	4,6 / 13,7 / 22,8 A	7,6 A
OUTPUT		
Power rating	1 / 3 / 5 KVA	5 KVA
Voltage	230VAC	400VAC
Frequency	50-60Hz	50-60Hz
Current	4,34 / 13,05 / 21,7 A	7,2 A
ENVIRONMENTAL		
Ambient Temperature	0°C to 30°C	0°C to 30°C
Operating Humidity	< 95 %	< 95 %
Altitude	<1000m	<1000m
Storage temperature	10°C to +50°C	10°C to +50°C
Efficiency at full load	>95%	>95%
Form Factor	3U / 5U / 5U Rack Mountable	8U Rack Mountable